11 ALL-NEW ENGINE

The CFORCE 625 is powered by an all-new 580cc, four-stroke, four-valve, EFI, liquid-cooled engine, built upon more than 2 decades of continuous innovation of liquid-cooled technology from CFMOTO. Powerful torque with 30kW output is put to work by the CVTech Transmission and centrifugal clutch. With quick and responsive engagement, the CFORCE 625 produces smooth acceleration—from 0-50m in only 4.5 seconds. High- and low-range options along with reverse allow the CFORCE 625 to make traction over a variety of terrain, from deserts to mountains, with responsive power and steady control.

27 INDEPENDENT SUSPENSION

Revised suspension features independent front and rear A-arms with preload-adjustable shock absorbers with 160mm wheel travel up front, and 210mm in the rear. Together with 270mm of ground clearance, the CFORCE 625 is ready to conquer technical terrain, steep slopes and trail obstacles with ease. Tune the shocks for advanced performance in varying conditions with 5-way spring-preload adjustability, allowing the suspension to soak up the bumps in even the roughest terrain. With less impact transferred to the body, you can ride in more comfort than ever before; let the CFORCE 625 do the work while you focus on the trail and enjoy the smooth ride.

3 EPS SYSTEM

The intelligent speed-sensitive EPS [Electronic Power Steering] system automatically responds to vehicle speed and provides precise steering aid to the rider. At low speed, steering remains light and effortless, making it easy to maneuver in tight areas. At higher speeds, steering is responsive and stable, enhancing rider confidence when tackling difficult terrain and trail obstacles. The ability to make effortless quick maneuvers, such as dodging an unexpected object in its path, helps to further improve safety.



Overall Dimensions

 Length x Width x Height
 2035x1180x1220 mm
 T: 2235x1180x1390 mm

 Wheelbase
 1280 mm
 T: 1480 mm

 Seat Height
 530 mm

 Minimum Ground Clearance
 270 mm

 Minimum Turning Diameter
 7.25 m
 T: 7.4 m

 Curb Weight
 375 kg
 T: 395 kg

 Payload Capacity
 230 kg



ngine

Engine Type Single-cylinder, Liquid cooled, 4-stroke, SOHC, 4-Valve

Displacement 580 cc

Transmission CVT



ssis

Drive Switchable 2WD/4WD

rake Four-wheel Disc-brake (CBS)

spension Front/Rear: Double A-arm independent suspension

k Absorber Front/Rear: Coil spring + oil damping

s Front: 12x6.0 AT Rear: 12x7.5 AT

Front: AT 25x8.0 Rear: AT 25x10,0-12



No. 116, Wuzhou Road, Yuhang Economic Development Zone Hangzhou 311100, Zhejiang Province.

Tel: 86-571-89265799 Instagram: cfmoto_world YouTube: CFMOTO
Email: export@cfmoto.com Facebook: CFMOTO_Official
Global.cfmoto.com Twitter: CFMOTO_Official

Copyright Zhejiang CFMOTO Power co., Ltd, 2019. All rights reserved. Vehicle specifications are subject to change without notice. Imagery may not reflect most current product specifications. CFMOTO reserves the right to make improvements and/or design changes without any obligation to modify previously sold, assembled or fabricated equipment.





